Certificate of Compliance

Certificate Number 130206 - E198546

Report Reference E198546, December 23rd, 2005

Issue Date 2006 February 13



Issued to:

GEFRAN SPA

VIA SEBINA 74

25050 PROVAGLIO D'ISEO BRESCIA ITALY

This is to certify that representative samples of Programmable controllers,

Cat. No. GFX-M2, GFX-S2, GFX-E2, followed by B15, 5, 10, 15, R, RR or CC, followed by 0, 230 or 440, followed by M, P, C or D, followed by 0, D, R or C, followed by RR, followed by P, followed by 0, C0, CV, IM or PO

Have been investigated by Underwriters Laboratories Inc.® in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 508 - Industrial Control Equipment

CSA C22.2 No. 14-M05 - Industrial Control Equipment

Additional Information:

See Addendum for Electrical Ratings

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and "US" identifiers: c the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product

Issued by:

Nadia Andreola

Nadia Andreola, Engineer

Reviewed by:

Matter Redaelli

Matteo Redaelli, Team Ldr Engineer

UL International Italia Srl

UL International Italia Srl Any information and documentation provided to you involving UL Mark services are provided on behalf of Underwriters Laboratories Inc. For questions in Italy, you may call +39 079 2636600.

Certificate of Compliance

Certificate Number 130206 - E198546

Report Reference E198546, December 23rd, 2005

Issue Date 2006 February 13



This is to verify that representative samples of the product as specified on this certificate were tested according to the current UL, cUL requirements.

RATINGS:

230 or 440 Vac, 5 A up to 13A, 50-60Hz Power supply:

24 Vdc ±25%, 5W max. Remote Class 2 Source Control input:

or limited voltage limited current.

24 Vdc, 8 mA Logic input

Output ratings: Relay: 250 Vac, 3A, resistive. Three relays maximum provided

Logic: 24 Vdc, 35 mA

One logic output + Two relays provided

Continuous: 0-10 V

0-20 mA

40°C Operating Surrounding air:

Issued by:

Nadia Andreola, Engineer

Reviewed by:

Matteo Redaelli, Team Ldr Engineer

UL International Italia Srl

UL International Italia Srl Any information and documentation provided to you involving UL Mark services are provided on behalf of Underwriters Laboratories Inc.UL International Italia Sci